



P34 PROFESSIONAL PHOTOMETER

WALLACE & TIERNAN® ANALYZERS/CONTROLLERS

The mobile photometer Wallace & Tiernan® P34 Professional measures up to 34 parameters in a single device, the most important parameters for water treatment. It meets all the requirements of modern water analysis. The most frequently used reagent tablets are included in the scope of delivery.

The device has a backlit display. Measuring range, reagent type as well as an automatic countdown timer for accurate response times are displayed. The internal memory stores up to 1,000 events with date, time and sample ID. These data can be retrieved at any time and transferred via an optional infrared module.

Zero Setting (OTZ)

Certain instruments have a One Time Zero (OTZ) function, making it unnecessary to zero the instrument between each test. This allows multiple tests to be performed using the same blank/zero sample until a new parameter is selected.

PARAMETERS

The photometer P34 Professional serves, among others, to detect alkalinity, aluminium, bromine, chlorine, chlorine dioxide, chlorite, cyanuric acid, iron, urea, hardness, iodine, copper, sodium hypochlorite, ozone, PHMB, phosphate, pH, oxygen, acid demand, sulphate and hydrogen peroxide using various methods.

Key Benefits

- Intuitive, fast operation due to Zero Setting
- User interface in several languages
- Backlit display
- Storage for up to 1000 data sets
- Waterproof housing (IP 68), floating

Optional infrared interface

The optional infrared interface module available (IRiM) uses infrared technology to transmit test data to one of 3 interfaces.

TECHNICAL DATA

Display: Graphic display

Interface:

IR interface for data transfer

RJ45 connector for internet updates

Light source:

light-emitting diode - photosensor - pair arrangement
in a transparent measurement chamber

Wavelength ranges:

$\lambda_1 = 530 \text{ nm IF } \Delta \lambda (\text{nm}) = 5$

$\lambda_2 = 560 \text{ nm IF } \Delta \lambda (\text{nm}) = 5$

$\lambda_3 = 610 \text{ nm IF } \Delta \lambda (\text{nm}) = 6$

IF = Interference filter

Operation:

Acid and solvent resistant touch-sensitive keyboard
with integral beeper as acoustic indicator

Power supply:

4 batteries (type AA/LR6)

lifetime: approx. 26 h continuous use or 3500 tests

Auto off:

20 min after last function

30 sec acoustical signal before switch off

Storage: approx. 1000 data sets

Dimensions (H x W x L):

Unit: 210 x 95 x 45 mm

Case: 395 x 295 x 106 mm

Weight: approx. 450 g

Ambient conditions:

Temperature: 5 - 40 °C

rel. humidity: 30 - 90 %, non-condensation

Language options:

English, German, French, Spanish, Italic, Portuguese,
Polish and Indonesian

Water proof:

IP 68 (1 h at 0.1 m), floating

SCOPE OF SUPPLY:

Equipment	No.
Photometer in plastic case	1
Batteries, 1.5 V	4
DPD No. 1 tablets	100
DPD No. 3 tablets	100
Phenol Red/Photometer tablets	100
Alka-M tablets	100
Glycin tablets	100
Screws	4
Screw driver	1
Battery compartement cover	1
Beaker, 100 ml	1
Syringe, 5 ml	1
Round vials with cap and sealing ring	3
Cleaning brush	1
Stirring rod	1
Instruction manual	1
Guarantee declaration	1
Certificate of compliance	1



Auf der Weide 10, 89312 Günzburg, Germany

+49 (8221) 904-0 www.evoqua.com

Wallace & Tiernan is a trademark of Evoqua, its subsidiaries or affiliates, in some countries.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2016 Evoqua Water Technologies GmbH Subject to change without notice WT.050.312.000.DE.PS.0716

Wallace & Tiernan® Products worldwide

Australia

+61 3 8720 6597
info.au@evoqua.com

Canada

+1 905 944 2800
canadainfo@evoqua.com

China

+86 21 6057 7247
sales.cn@evoqua.com

France

+33 1 41 15 92 20
wtfra@evoqua.com

Germany

+49 8221 9040
wtger@evoqua.com

Singapore

+65 6830 7165
sales.sg@evoqua.com

UK

+44 1732 771777
info.uk@evoqua.com

USA

+1 856 507 9000
wt.us@evoqua.com